

Display Device

BACview⁶

Locally access controllers and operational properties or manage a small facility with the easy-to-use BACview⁶ keypad/display. It simply plugs into an Rnet connection and allows you to display and modify user-defined properties without any computer software. The BACview⁶ features a numeric keypad, directional keys, and four programmable function keys. A large 4-line by 40-character backlit LCD display is provided for easy reading even in poor lighting conditions. The device also includes an alarm indicator light and audible warning.



Key Features and Benefits

- Compatible with I/O Zone, I/O Flex, and I/O Pro Controllers.
- Flexible design allows panel or wall mounting; can be located up to 500 feet from the control panel.
- Can share Rnet (OEMCtrl sensor network) with up to 5 Room Sensors.
- Backlit LCD display enhances reading even in poor lighting conditions.
- Allows customization of building properties for each project using industry-standard HTML.
- Password protection provides security.

Specifications

Power	Supplied by the 4 conductor cable (+12Vdc @ 250mA).
Physical	Rugged aluminum enclosure for protection and easy backplane mounting.
Operating Range	32° to 130°F (0° to 54.4°C), 10%-90% RH non-condensing.
Backlit LCD Display	4-line by 40-character display.
Hardware Compatibility	All controllers with Rnet capability.
Status Indication	HTML programmable 4-line by 40-character back lit LCD display with alarm LED indicator.
Protection	Provides 15KVESD protection to the enclosure.
Listed by	UL 916 (PAZX), CE (1997), FCC Part 15 - Subpart B - Class A.
Weight	1.2 lbs. (0.54 Kg)
Mounting	Wall or panel mounting; remote mounting up to 500 feet. Standard J box may be used.
Overall Dimensions	9-5/8" (width) by 4-15/16" (height) by 1" (recommended panel depth). 245mm (width) by 125mm (height) by 25mm (recommended panel depth).